

2 MP EXIR VF Turret Camera



Key Features

- 2 MP high-performance CMOS
- 1920 × 1080 resolution
- Vari-focal Lens 2.7-13.5mm Motorized, Auto focus)
- Day/Night switch
- EXIR 2.0, smart IR, up to 70 m IR distance
- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)
- IP66



Technical Specifications

Camera	
Image Sensor	2 MP CMOS image sensor
Signal System	PAL/NTSC
Resolution	1920 (H) × 1080 (V)
Min. Illumination	Ultra low light 0.005 Lux
Shutter Time	1/25 (1/30) s to 1/50,000 s
Lens	Vari-focal Lens 2.7-13.5mm Motorized, Auto focus)
Horizontal Field of View	102.4° to 31°
Day & Night	IR cut filter
Synchronization	Internal synchronization
Video Frame Rate	PAL: 1080p@25fps NTSC: 1080p@30fps
Menu	
AGC	High/Medium/Low/Off
D/N Mode	Auto/Color/BW (Black and White)
BLC	Support
DWDR	Support
Functions	Brightness, Sharpness, DNR, Mirror, Smart IR
General	
Operating Conditions	-40 °C to 60 °C (-40 °F to 140 °F), Humidity: 90% or less (non-condensation)
Power Supply	12 VDC ±15% Power Consumption Max. 7,7 W
Protection Level	IP66, Material Enclosure Plastic & Body Metal
IR Range	Up to 70 m
Dimensions	∅ 123.86 mm × 103.9 mm
Weight	606 g